

Table of Contents

0 Preface

1 Overview

- 1.1 Total System
- 1.2 Advantages and Disadvantages of the RCS versus AR
- 1.3 Features of the Linac Design
- 1.4 Features of the RCS Design
- 1.5 Features of the MR Design
- 1.6 Summary

2 Beam Dynamics Design

- 2.1 Linac
 - 2.1.1 Fundamental design
 - 2.1.2 Ion Source, LEPT, RFQ
 - 2.1.3 MEPT1, DTL, SDTL
 - 2.1.3.1 MEPT1
 - 2.1.3.1.1 Beam-line design
 - 2.1.3.1.2 Chopper Design
 - 2.1.3.1.3 Analysis on unstable particles
 - 2.1.3.1.4 Buncher design
 - 2.1.3.1.5 Analyzer line design
 - 2.1.3.1.6 Upgrade with an anti-chopper
 - 2.1.3.1.7 Beam dynamics simulation
 - 2.1.3.2 DTL and SDTL
 - 2.1.3.2.1 Introduction
 - 2.1.3.2.2 Cell geometry
 - 2.1.3.2.3 DTL tank parameters
 - 2.1.3.2.4 Focusing design
 - 2.1.3.2.5 Matching between the DTL and SDTL, and SDTL tank parameters
 - 2.1.3.2.6 Beam loading of a chopped beam
 - 2.1.3.2.7 Beam simulation
 - 2.1.4 MEPT2, ACS
 - 2.1.4.1 ACS
 - 2.1.4.2 MEPT2
 - 2.1.4.3 Simulation from the DTL to the ACS
 - 2.1.5 BT to 3-GeV Ring
 - 2.1.5.1 Overview
 - 2.1.5.2 Design concept of L3BT sections
 - 2.1.5.3 Beam collimation
 - 2.1.5.4 Debuncher design
 - 2.1.5.5 Beam simulation with space charge
 - 2.1.6 Superconducting Linac and MEPT-3
 - 2.1.6.1 Design Overview of the Superconducting Linac Section
 - 2.1.6.2 Beam Simulation of the Superconducting Linac Section

- 2.1.6.3 Design of the MEBT-3 (Medium Energy Beam Transport-3)
- 2.2 3GeV Rapid-Cycling Synchrotron (RCS)
 - 2.2.1 Introduction
 - 2.2.2 Beam Optics Design
 - 2.2.2.1 Introduction
 - 2.2.2.2 Tunability and Structure Resonance
 - 2.2.2.3 Closed orbit distortion and correction
 - 2.2.2.4 Chromatic Behavior and Correction
 - 2.2.2.5 Fringe field effects and Dynamic aperture
 - 2.2.2.5.1 Motivation of study
 - 2.2.2.5.2 Subject of the investigation
 - 2.2.2.5.3 Dynamic aperture of the 3GeV RC-synchrotron
 - 2.2.2.5.4 Conclusion
 - 2.2.3 Injection, Beam Collimation and Extraction
 - 2.2.3.1 Injection
 - 2.2.3.1.1 Introduction
 - 2.2.3.1.2 Parameters for painting injection
 - 2.2.3.1.3 Design of the bump magnets system
 - 2.2.3.1.3.1 Outline of the injection bump orbit
 - 2.2.3.1.3.2 Fixed closed-orbit bump magnets at the injection period
 - 2.2.3.1.3.3 Horizontal painting bump magnets
 - 2.2.3.1.3.4 Vertical painting magnets
 - 2.2.3.1.4 Design of the magnetic field
 - 2.2.3.1.4.1 Magnetic Stripping of H⁺ Ions
 - 2.2.3.1.4.2 Fraction of excited H⁰
 - 2.2.3.1.4.3 Trajectory of stripped electrons
 - 2.2.3.1.4.4 β and tune Modulation by Bump Orbit
 - 2.2.3.2 Beam Collimation
 - 2.2.3.2.1 Overview
 - 2.2.3.2.2 Collimator System Design
 - 2.2.3.2.3 Simulation Results
 - 2.2.3.2.4 Conclusion
 - 2.2.3.3 Extraction
 - 2.2.3.3.1 Overall Design
 - 2.2.3.3.2 Kicker Magnet Layout
 - 2.2.3.3.3 Septum Magnet Layout
 - 2.2.4 RF Acceleration
 - 2.2.4.1 RF Voltage Program
 - 2.2.4.2 Longitudinal emittance control
 - 2.2.4.3 Beam loading
 - 2.2.4.4 Beam loading compensation
 - 2.2.4.5 Transient beam loading
 - 2.2.5 Emittance Blow-up and Halo-formation
 - 2.2.5.1 Introduction
 - 2.2.5.2 Machine Model
 - 2.2.5.3 Computer Simulation and Code Benchmarking
 - 2.2.5.4 Physics of Emittance blow-up and Halo-formation
 - 2.2.5.5 Beam Intensity and Tune
 - 2.2.5.6 Conclusion
 - 2.2.6 Beam Transport to Neutron and Muon Production Targets

- 2.2.6.1 Layout
- 2.2.6.2 Beam Optics
- 2.2.6.3 Distortion of Beam Orbit
- 2.2.6.4 Beam Loss
- 2.2.7 Beam Transport to 50-GeV MR
- 2.3 50-GeV Main Ring
 - 2.3.1 Introduction
 - 2.3.2 Beam Optics Design
 - 2.3.2.1 Basic Focusing Channel
 - 2.3.2.2 Emittance and Acceptance
 - 2.3.2.3 Tuning Knobs and its Optimization
 - 2.3.2.4 COD Correction
 - 2.3.2.5 Chromaticity Correction and Dynamic Aperture
 - 2.3.2.6 Fringe fields and dynamic aperture of 50GeV MR
 - 2.3.2.6.1 Analysis of the working point
 - 2.3.2.6.2 Intrinsic sources of magnetic field non-linearities / Order of Map
 - 2.3.2.6.3 Changing of the linear properties of MR and ‘detuning’ effects
 - 2.3.2.6.4 Analysis of dynamic aperture
 - 2.3.2.6.5 Conclusion
 - 2.3.3 Injection, Beam Collimation
 - 2.3.4 Fast Extraction
 - 2.3.5 Slow Extraction
 - 2.3.5.1 Introduction
 - 2.3.5.2 Slow Extraction Scheme
 - 2.3.5.3 Beam Loss Calculation at the ESS Wires
 - 2.3.5.4 Concluding Remarks
 - 2.3.6 RF Acceleration
 - 2.3.6.1 RF Voltage Program
 - 2.3.6.2 Emittance control
 - 2.3.6.3 Longitudinal Beam Loading
 - 2.3.6.4 Transient Beam Loading
 - 2.3.7 Emittance Growth, Beam Instability
 - 2.3.7.1 Space charge effects
 - 2.3.8 Electron Proton Two Stream Instability
 - 2.3.8.1 Electron cloud build-up and e-p instability
 - 2.3.8.2 Secondary Electron Emission from Metals and Graphites
 - 2.3.8.2.1 Sample Materials
 - 2.3.8.2.2 Experimental Set-up and the Conditions
 - 2.3.8.2.3 Measurement of Secondary Electron Yields and Surface Analyses
 - 2.3.8.2.4 Summary

3 Component Design, R&D Strategy & Results, Construction Status

- 3.1 Linac
 - 3.1.1 Ion Source
 - 3.1.2 Accelerating Structure and Beam Transport
 - 3.1.2.1 LEPT
 - 3.1.2.2 RFQ
 - 3.1.2.3 MEPT1
 - 3.1.2.3.1 Buncher

- 3.1.2.3.2 Chopper
- 3.1.2.3.3 Scraper
- 3.1.2.3.4 Beam monitors
- 3.1.2.3.5 Magnets for the MEBT1
- 3.1.2.3.6 Alignment
- 3.1.2.3.7 Beam test
- 3.1.2.4 DTL, SDTL
 - 3.1.2.4.1 Rf and mechanical features of the DTL and SDTL tanks
 - 3.1.2.4.2 RF contactor
 - 3.1.2.4.3 Vacuum and rf properties of the test tank
 - 3.1.2.4.4 Quadrupole magnet for the DTL
 - 3.1.2.4.5 Specification of all the Q-magnets
 - 3.1.2.4.6 Quadrupole doublets for the SDTL
 - 3.1.2.4.7 Pulsed-current power supply
 - 3.1.2.4.8 Breakdown test of the copper electrode
 - 3.1.2.4.9 Input-coupler for the DTL and SDTL
 - 3.1.2.4.10 High-power test of a model tank and SDTL
 - 3.1.2.4.11 Assembling of DTs for the first tank of the DTL
 - 3.1.2.4.12 Field stability in the DTL tank during operation
- 3.1.2.5 ACS
 - 3.1.2.5.1 Cavity Fabrication
 - 3.1.2.5.2 Cavity Design
- 3.1.2.6 Superconducting Linac
 - 3.1.2.6.1 General
 - 3.1.2.6.2 Lorentz Detuning and RF Control for Pulsed Operation
 - 3.1.2.6.3 Cavity Design
 - 3.1.2.6.4 Input Coupler
 - 3.1.2.6.5 Cavity Fabrication
 - 3.1.2.6.6 Cryomodule
 - 3.1.2.6.7 Cryogenics
- 3.1.2.7 BT to RCS
- 3.1.2.8 Alignment
- 3.1.3 RF Power Source
 - 3.1.3.1 Overview
 - 3.1.3.2 324-MHz Klystron
 - 3.1.3.3 972-MHz Klystron
 - 3.1.3.4 Klystron Power Supply
 - 3.1.3.5 Waveguides
 - 3.1.3.5.1 Waveguide layout
 - 3.1.3.5.2 Components of the waveguide system
 - 3.1.3.6 RF Drive and Control System
 - 3.1.3.6.1 RF Reference Distribution System
 - 3.1.3.6.2 Digital Rf feedback system
 - 3.1.3.6.3 Test of feedback system
 - 3.1.3.7 Chopper Driving System
- 3.1.4 Vacuum System
 - 3.1.4.1 Ion Source and LEPT, RFQ, MEBT
 - 3.1.4.2 DTL, SDTL, Periodic-Reverse Electrolytic Copper Plating
 - 3.1.4.3 ACS
- 3.1.5 Beam Instrumentation

- 3.1.5.1 Beam Instrumentation Layout around the LINAC
- 3.1.5.2 Beam Position Monitor (BPM)
- 3.1.5.3 Beam Current Monitor
- 3.1.5.4 Beam Phase Monitor
- 3.1.5.5 Beam Profile Monitor
- 3.1.5.6 Beam Loss Monitor
- 3.1.5.7 The monitors under designing
- 3.1.5.8 Conclusion
- 3.2 RCS
 - 3.2.1 Magnets and Power Supplies
 - 3.2.1.1 Design of RCS Magnets
 - 3.2.1.2 Resonant Network System
 - 3.2.1.3 Eddy Current Effect
 - 3.2.2 Injection, Beam Collimation, Extraction
 - 3.2.2.1 Research and Development of Long-Lived Thick Carbon Stripper Foils
 - 3.2.2.2 Kickers
 - 3.2.2.2.1 Design Concept
 - 3.2.2.2.2 Magnet
 - 3.2.2.2.3 Power Supply
 - 3.2.2.2.4 Transverse Emittance Increment
 - 3.2.2.2.5 Possibility of Up-grade
 - 3.2.2.3 Septum Magnets
 - 3.2.2.4 Bump Magnets
 - 3.2.2.4.1 Introduction
 - 3.2.2.4.2 Closed orbit bump magnets
 - 3.2.2.4.3 Painting bump magnets
 - 3.2.2.4.4 Septum magnets
 - 3.2.2.5 Collimator Hardware Design
 - 3.2.2.5.1 Radiation Shield Design of Collimator
 - 3.2.2.5.2 3GeV RCS Beam Collimator Design
 - 3.2.2.6 H0 Beam Dump System
 - 3.2.2.6.1 Overview
 - 3.2.2.6.2 Heating Design
 - 3.2.3 Vacuum System
 - 3.2.3.1 Vacuum chamber
 - 3.2.3.2 Alumina ceramic duct
 - 3.2.3.3 RF shield and TiN coating
 - 3.2.3.4 Vacuum pumps and components
 - 3.2.4 Beam Instrumentation
 - 3.2.4.1 Introduction
 - 3.2.4.2 Current Monitor
 - 3.2.4.2.1 Intensity Monitor
 - 3.2.4.2.2 Bunch Monitor
 - 3.2.4.3 Beam Loss Monitor
 - 3.2.4.3.1 Ionization type
 - 3.2.4.3.2 Color scintillator type
 - 3.2.4.4 Beam Position Monitor
 - 3.2.4.4.1 Pickup Electrode
 - 3.2.4.4.2 Signal Processing
 - 3.2.4.4.2.1 Heterodyne Processing

- 3.2.4.4.2 Log-Amp method
 - 3.2.4.4.3 Digital Processing
 - 3.2.4.5 Beam Profile Monitor
 - 3.2.4.5.1 Destructive Beam Profile Monitor
 - 3.2.4.5.2 Non-destructive Beam Profile Monitor
 - 3.2.4.6 Tune Monitor
 - 3.2.5 Beam Transport Components to Neutron and Muon Production Targets
 - 3.2.5.1 Magnets
 - 3.2.5.2 Beam Monitors
 - 3.2.5.3 Vacuum Components
 - 3.2.5.4 Beam Collimators
 - 3.2.5.5 Beam Dump
 - 3.2.5.6 Beam Line inside the Material and Life Science Facility
 - 3.2.6 Beam Transport Components to 50-GeV Synchrotron
 - 3.2.6.1 General
 - 3.2.6.2 Magnets and Power Supply
 - 3.2.6.3 Vacuum System
 - 3.2.6.4 Monitor System
 - 3.2.6.5 Beam Scraper
- 3.3 50GeV MR
 - 3.3.1 Magnets and Power Supplies
 - 3.3.1.1 Magnets
 - 3.3.1.2 Power Supplies
 - 3.3.2 Injection, Extraction, Beam Collimation, Beam Abort, Beam Dump
 - 3.3.2.1 Kicker
 - 3.3.2.2 Septum
 - 3.3.2.2.1 Types of Septum Magnet
 - 3.3.2.2.2 Slow Extraction Septum Magnet
 - 3.3.2.2.3 Fast extraction septum magnet
 - 3.3.2.2.4 Electrostatic Septum
 - 3.3.2.3 Beam halo scraper
 - 3.3.2.4 Beam Abort and Dump
 - 3.3.3 Vacuum System
 - 3.3.3.1 Standard vacuum chamber
 - 3.3.3.2 Vacuum chamber in dipole and quadrupole magnets
 - 3.3.3.3 Bellows
 - 3.3.3.4 Surface treatment of vacuum chambers
 - 3.3.4 Beam Instrumentation
 - 3.3.4.1 Introduction
 - 3.3.4.2 Current Monitor
 - 3.3.4.3 Beam Loss Monitor
 - 3.3.4.4 Beam Position Monitor (BPM)
 - 3.3.4.5 Beam Profile Monitor
 - 3.3.4.6 Summary
- 3.4 RF Acceleration System
 - 3.4.1 Synchrotron Cavities
 - 3.4.1.1 Magnetic Alloy
 - 3.4.1.2 Cut Core
 - 3.4.1.3 Cooling
 - 3.4.1.4 The MR Cavity

- 3.4.1.5 The RCS Cavity
- 3.4.2 RF Power Amplifier
- 3.4.3 Anode Power Supply
- 3.4.4 Radio-frequency Signal Generator
- 3.4.5 Beam Control
 - 3.4.5.1 Orbit Control
 - 3.4.5.2 Phase Control
 - 3.4.5.3 RF Feed-forward System
- 3.5 Synchronization

4 Tunnel Design, Component Layout, Maintenance Scenario

- 4.1 Linac
 - 4.1.1 Tunnel Design
 - 4.1.2 Component Layout
 - 4.1.3 Maintenance Scenario
- 4.2 RCS
 - 4.2.1 Tunnel Design
 - 4.2.2 Component Layout
 - 4.2.3 Maintenance Scenario
- 4.3 MR
 - 4.3.1 Tunnel Design
 - 4.3.2 Component Layout
 - 4.3.3 Maintenance Scenario

5 Control System

- 5.1 Introduction
- 5.2 EPICS
 - 5.2.1 Basic architecture of the control system
 - 5.2.2 What is EPICS
 - 5.2.3 Usable Modules for Device control
- 5.3 Network
 - 5.3.1 Functional Requirements
 - 5.3.2 Preliminary design of the control network
- 5.4 Higher Level Applications and Operator Interface
 - 5.4.1 Application Software on IOC
 - 5.4.2 Application on Client
 - 5.4.3 Features of Application Development Environment (ADE)
 - 5.4.4 Basic Operational Applications
- 5.5 Database
 - 5.5.1 General Requirements
 - 5.5.2 Use of EPICS database and DBMS in the Joint Project
- 5.6 Personnel Protection System

6 Timing System

- 6.1 Basic design

6.2 Timing chart of each accelerator

7 Building, Cooling Water, Electricity, Air-Conditioning

7.1 Linac

7.1.1 Building

7.1.2 Cooling Water

7.1.3 Electricity

7.1.4 Air-Conditioning

7.2 RCS

7.2.1 Building

7.2.2 Utilities

7.2.2.1 Electric Power

7.2.2.2 Cooling Water

7.2.2.3 Air-conditioning System

7.3 MR

7.3.1 Carrying Buildings

7.3.2 Power Supply Building and Electric Powers

7.3.3 Machine buildings, Cooling Water and Air-Conditioning

8 Radiation Safety

8.1 Introduction

8.1.1 Design principle

8.1.2 Evaluation of radiation and radioactivity

8.2 Shielding Design for the Linac

8.2.1 Beam loss assumption

8.2.2 Bulk shielding calculations

8.2.3 Activation of air in the tunnel

8.2.4 Activation of the cooling water

8.3 3-GeV synchrotron

8.3.1 Bulk shield calculations

8.3.2 Activation of air and cooling water in the tunnel

8.4 50-GeV Synchrotron

8.4.1 Dose evaluation on the ground surface and the site boundary

8.4.2 Shielding wall design of the 3-50 BT line

8.4.3 Further items for the radiation safety design

8.5 Proton Beam Line between 3-GeV RCS and Materials and Life Science Facility

8.6 Annual Production of Radioactive Gas and Liquid and the Annual Total Exhaust

8.7 Effective Dose due to an Abnormal Incident

9 Schedule and Commissioning Strategy

9.1 Schedule

9.2 Commissioning strategy

9.2.1 Beam parameters for commissioning

9.2.2 Timing System

9.2.3 Machine protect/others

10 PARAMETER LIST

10.1 LINAC

- 10.1.1 GENERAL
- 10.1.2 ION SOURCE
- 10.1.3 LEBT
- 10.1.4 RFQ
- 10.1.5 MEBT1
- 10.1.6 DTL
- 10.1.7 SDTL
- 10.1.8 MEBT2
- 10.1.9 ACS
- 10.1.10L3BT
- 10.1.11RF POWER SOURCE

10.2 3 GeV rapid-cycling Synchrotron Parameters and Specifications

- 10.2.1 General
- 10.2.2 Optics and Dynamics
- 10.2.3 Magnets and Power Supplies
- 10.2.4 Injection
- 10.2.5 Collimator
- 10.2.6 Extraction
- 10.2.7 RF Cavity
- 10.2.8 Beam Monitors
- 10.2.9 Vacuum System

10.3 50 GeV MR Parameters and Specifications

- I. General
- II. Optics and Dynamics
- III. Magnets and Power Supplies
- IV. RF System
- V. Slow Extraction
- VI. Vacuum System
- VII. Beam Monitors
- VIII. Tunnel and Radiation Shield
- IX. General Layout of the 50 GeV MR

List of Authors